


# ロックンギキー LS, LK


Locking Key LS, LK

RoHS指令適合品



LS

- 表 ノブ knob : 艶消し黒色ナイロン樹脂PA6 (ガラス繊維強化)  
Glass-fiber Nylon resin  
ネジ screw : 鋼材SUM22L・三価クロメート Steel Trivalent Chromate



LK

- 表 ノブ knob : 艶消し黒色ナイロン樹脂PA6 (ガラス繊維強化)  
Glass-fiber Nylon resin  
ネジ screw : 黄銅C3604B brass

品番	M	L	D	D1	H	h	Unit : mm (φ)
LS-4×6	M 4×P0.7	6	20	9.5	11	0.4	4
LS-4×10		10					7
LS-5×10	M 5×P0.8	10	26	11.0	6		
LS-5×16		16			7		
LS-6×10	M 6×P1.0	10	32	13.0	8		
LS-6×16		16			10		
LS-6×25	M 6×P1.0	25	40	15.5	12		
LS-8×25		25			16		
LS-8×40	M 8×P1.25	40	40	17	20		
LS-8×16-B		16			15		
LS-8×25-B	25	16					
LS-8×40-B	40	22					
LS-10×20	M10×P1.5	20	40	15.5	25		
LS-10×30		30			27		
LS-10×40		40			31		

品番	M	β	D	D1	H	h	Unit : mm (φ)
LK-4	M 4×P0.7	6	20	9.5	11	0.4	3
LK-5	M 5×P0.8	5	26	11.0	13		4
LK-6	M 6×P1.0	8	32	13.0	15		7
LK-B-A	M 8×P1.25		40	15.5	17		8
LK-B-B			40	15.5	17		10

注意事項 使用温度 max80℃ min-20℃